hitrolink

HTI-A-SP08

8" Multi-function speaker



Features

- Full frequency speaker for conference use, with full mid frequency and extremely high vocal reproduction.
- Professional design of the box space, effective resonance with the unit, high frequency response, and high efficiency.
- Adopting high-quality units, high sensitivity, and high power.
- Accurate frequency division circuit, clear and transparent sound quality.
- The sound is clean and powerful, with a high degree of reproduction.
- The high-end and exquisite appearance showcases the wisdom of craftsmen.
- Circuit protection: high-frequency protection.

Conference Audio System

Technical Parameters	
System type	1*8" two-way full-range speaker
Tweeter	25mm voice coil compression unit
Woofer	35mm voice coil driver
Power output	150W
Peak power	600W
Nominal impedance	8Ω
Nominal sensitivity	93dB(1W@1m)
Maximum sound pressure level	120dB
Frequency bandwidth	75Hz-19KHz (±3dB)
Material	CNC manufacturing, high-density board
Crossover Mode	Passive
Connection	NLV4MP
Dimension	240*255*400mm
Net Weight	10kg
Gross Weight	11.1kg

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



Zhejiang Huachuang Vision Technology Co., Ltd.