

## HTI-A-8008BS

Delegate Paging Microphone



### Features

- Adopts advanced and stable EEPROM chip and digital conference technology to realize digital signal transmission and processing;
- High-fidelity audio transmission technology, 48KHz audio sampling frequency, frequency response 20Hz-20KHz;
- High-sensitivity pickup design, built-in AGC function, and the effective pickup distance up to 50-60cm;
- Equipped with a 2.4" LCD high-brightness display, which can display system signal, channel, ID address, battery power, WiFi channel and speaking time;
- Built-in 3200mAh large-capacity lithium battery, with dual charging function, supports USB charging and charging box charging;
- The system can connect to 4 chairman units at the same time. The chairman unit has the priority function and can also shut down other delegate units that are speaking.
- With ultra-long transmission and reception distance, the effective distance can reach 80 meters in ideal environment
- Super anti-interference ability, which can effectively isolate signal interference from mobile phones, radio waves, Bluetooth, WiFi, etc.
- Equipped with 1 TYPE-C interface, which can be used for charging or non-disassembly device upgrade and maintenance

# Conference Audio System

Technical Parameters	
Display	2.4" LCD
Microphone Type	Cardioid directional electret
Response frequency	20Hz-20KHz
Sensitivity	-37dB ± 2dB
THD	≤0.05%;
SNR	>90dB
Dynamic range	>96dB
Maximum SPL	125dB(THD<3%)
Charging port	USB Type-C
Battery	3200mAh
Working Power	DC3.7V
Base Dimension	130*100*55mm
Net weight	0.9kg
Gross weight	1.4kg

Design and specifications are subject to change without notice.

Pictures in the document are for reference only, and the actual product shall prevail.