

HTI-A-8008AS

Delegate Paging Microphone



Features

- Adopts advanced and stable EEPROM chip and digital conference technology to realize digital signal transmission and processing;
- High-fidelity audio transmission technology, 48KHz audio sampling frequency, frequency response 20Hz-20KHz;
- High-sensitivity pickup design, built-in AGC function, and the effective pickup distance up to 50-60cm;
- Equipped with a 2.4" LCD high-brightness display, which can display system signal, channel, ID address, battery power, WiFi channel and speaking time;
- Built-in 3200mAh large-capacity lithium battery, with dual charging function, supports USB charging and charging box charging;
- The system can connect to 4 chairman units at the same time. The chairman unit has the priority function and can also shut down other delegate units that are speaking.
- With ultra-long transmission and reception distance, the effective distance can reach 80 meters in ideal environment
- Super anti-interference ability, which can effectively isolate signal interference from mobile phones, radio waves, Bluetooth, WiFi, etc.
- Equipped with 1 TYPE-C interface, which can be used for charging or non-disassembly device upgrade and maintenance

Conference Audio System

| Technical Parameters | |
|----------------------|-------------------------------|
| Display | 2.4" LCD |
| Microphone Type | Cardioid directional electret |
| Response frequency | 20Hz-20KHz |
| Sensitivity | -37dB ± 2dB |
| THD | ≤0.05%; |
| SNR | >90dB |
| Dynamic range | >96dB |
| Maximum SPL | 125dB(THD<3%) |
| Charging port | USB Type-C |
| Battery | 3200mAh |
| Working Power | DC3.7V |
| Base Dimension | 130*100*55mm |
| Net weight | 0.9kg |
| Gross weight | 1.4kg |

Design and specifications are subject to change without notice.

Pictures in the document are for reference only, and the actual product shall prevail.