

## HTI-A-HK400

2 × 400W professional power amplifier



### Features

- Three classic working modes: stereo, mono and bridge, which can meet the matching of different systems;
- LED indicator to monitor the working status of the power amplifier;
- 8Ω stereo power 2×400W, 4Ω stereo power 2×800W, and 8Ω bridge power 1200W;
- High signal-to-noise ratio and extremely low noise;
- Total harmonic distortion <0.05%;
- Damping coefficient >300;
- Dynamic range ≥95dB;
- Signal-to-noise ratio ≥95dB;
- Input impedance balanced 20KΩ/unbalanced 10KΩ;

# Conference Audio System

Technical Parameters	
Working power	AC100~240V
Response frequency	20Hz-20KHz;
Input resistance	10K $\Omega$ unbalanced, 20K $\Omega$ balanced
Damping factor	>300@8 $\Omega$ ;
THD	$\leq$ 0.01%;
Indicator	Support
Minimum load impedance	stereo>3.2 ohm
8 $\Omega$ stereo power	2*400W
4 $\Omega$ stereo power	2*800W
8 $\Omega$ bridge power	1200W
Color	Black
Dimension	433*310*90mm
Net weight	14.2kg
Gross weight	15.4kg

Design and specifications are subject to change without notice.

Pictures in the document are for reference only, and the actual product shall prevail.