

HTI-A-HK200

2×200W professional power amplifier



Features

- Three classic working modes: stereo, mono and bridge, which can meet the matching of different systems;
- LED indicator to monitor the working status of the power amplifier;
- 8Ω stereo power 2×200W, 4Ω stereo power 2×400W, and 8Ω bridge power 600W;
- High signal-to-noise ratio and extremely low noise;
- Total harmonic distortion <0.05%;
- Damping coefficient>300;
- Dynamic range ≥95dB;
- Signal-to-noise ratio ≥95dB;
- Input impedance balanced 20KΩ/unbalanced 10KΩ;

Conference Audio System

| Technical Parameters | |
|-------------------------|--|
| Working power | AC100~240V |
| Response frequency | 20Hz-20KHz; |
| Input resistance | 10K Ω unbalanced, 20K Ω balanced |
| Damping factor | >300@8 Ω ; |
| THD | \leq 0.01%; |
| Indicator | Support |
| Minimum load impedance | stereo>3.2 ohm |
| 8 Ω stereo power | 2*200W |
| 4 Ω stereo power | 2*400W |
| 8 Ω bridge power | 600W |
| Color | Black |
| Dimension | 433*310*90mm |
| Net weight | 13.4kg |
| Gross weight | 14.3kg |

Design and specifications are subject to change without notice.

Pictures in the document are for reference only, and the actual product shall prevail.