

# HTI-UC600

1080P USB PTZ Camera



- 1/2.8" HD CMOS, 2.13MP pixels, 1080P@60fps video output.
- 4.7~47mm auto focus length, 10x optical zoom.
- Adopts standard UVC protocol, without installing drive, real plug and play.
- Multi-function IR remote controller provides convenient operation.
- Pan:-90°~+90°, Tilt:-20°~+20°, flexible angle adjustment.
- Horizontal mount/Ceiling mount/Wall mount.

## Product Overview

The HTI-UC600 is a 1080P PTZ USB camera which provides users with the ultimate video conferencing experience. To provide participants high quality conference images, HTI-UC600 adopts High quality HD CMOS sensor with 1/2.8 inch and 2.13 million effective pixels. The flexible angle adjustment also improve the video effects by capturing the speakers in a wide range. Moreover, the original electronic anti-shake technology ensures the image output more stable. Also, the USB 2.0/3.0 interface makes HTI-UC600 transmit the video images and control the console at the same time.

## Technical Specification

### Video

Image Sensor	1/2.8" CMOS
Effective Pixels	2.13MP
Resolution	1080P60fps, 1080P25/30fps, 720P60fps, 720P25/30fps
Video Codec	H.264, MJPEG, YUV
Lens Zoom	10x
Field of View	6.43° ~ 60.9°
Focus	Manual/Auto
Noise Reduction	2D NR/3D NR
Others	Auto Gain Control, WDR, White Balance

### PTZ

Pan	Pan: -90°~+90°
Tilt	Tilt: -20°~+20°
Presets	255

### USB

PTZ Control	Support
-------------	---------

### Interfaces

Video Output	1 × USB 3.0/2.0
Serial Port	1 × RS232

### Installation

Installation	Horizontal/Ceiling/Wall
--------------	-------------------------

### Physical Features

Power Supply	12V DC (10.8~13.0V DC)
Dimensions(W×D×H)	218mm × 119mm×119mm(8.6" × 4.7" × 4.7")
Weight	1.8kg (3.97lb)
Color	Black