Hitrolink Webcam DATASHEET

HTI-UC340

hitrolink

2K webcam



UC340 is a new generation of Hitrolink webcam product. 2K resolution with high cost-performance to provide more clear video quality than 1080P webcam. It is light and environmental friendly designed, has built-in mic and privacy cover, choose UC340 to be your good partner in video chat.



- A. 5MP camera
- B. 3 meter Omni-mic
- C. Stands
- D. 360° Rotatable Head
- E. Indicator

FEATURES SPOTLIGHT

2K resolution, Support up to 2k@30 fps video output, compatible with lower resolution.

Built-in omnidirectional microphone, support clear voice pick up in 5 meters.

Plug and play, one USB 2.0 interface to support power supply, video and audio transmission.

Wide HFOV up to 79°, support digital zoom and auto focus.

Low illumination, clear image in low light environment.

Standard stands, easy to install.

Scenario

Online meeting, Hybrid learning, Remote interview, Live streaming.

Hitrolink Webcam DATASHEET

SPECIFICATION

Video parameter

MJPEG/H264: 2560*1440@30fps, 1920*1080@30fps,1280*720@30fps, 640*480/360@30fps

YUV: 640*480/360@30fps

SNR ≥50dB

USB output USB2.0/UVC1.0/1.1; MJPEG, 2K@30fps

Auto focus Support distance from 0.1-5 meters

Driver Support Windows\Linux\Mac OS\Android system. Etc. UVC protocol and driver free

FOV DFOV 88°, HFOV 79°

Exposure Auto, Exposure compensation, backlight compensation

Shutter 1/30s~1/10000s

Digital noise reduction 2D, 3D

White balance Support

Microphone parameter

Mic type Built-in omnidirectional microphone

Pick up distance 5 meters

Frequency 10-10K Hz

Sensitivity -24±3dB

S/N 60dB

Sampling rate 16 bit, 48KHz

Interface

Power supply USB2.0

Video/Audio USB2.0

Physicals

Power supply DC 5V , 2W

Temperature 0°C~+40°C

USB cable 1.5m

Dimension 109.5*66*52.5mm

Weight 170g

DIMENSIONS (mm[inch])





















